



FIG 1: American Type



FIG 2: European Type



FIG 3: Australian Type



FIG 4: British Type



FIG 5: Chinese Type



FIG 6: Korean Type



FIG 7: Argentinian Type





FIG 8: Japanese Type




FIG 9: Brazil Type




FIG 10: India Type




AC Plug-US




AC Plug-EU




AC Plug-SA




AC Plug-UK




AC Plug-CH




AC Plug-KR



AC Plug-AR



AC Plug-JP



AC Plug-BZ



AC Plug-IN

■Safety agency approvals:



■Specifications:

Model No.	GMPD45I*
AC input range	100~240VAC ; 47~63Hz ; 1.2-0.6A
DC Output	5V / 9V / 12V / 15V / 20V
Rated Current	PD: 5V 3A / 9V 3A / 12V 3A / 15V 3A / 20V 2.25A. QC: 5V 3A / 9V 3A / 12V 3A / 20V 3A
Leakage current	0.1mA Max.@ 240VAC/50Hz
Output Protection	Short circuit, over voltage, over current
Operating temperature	40°C to +70°C ; >40°C derating curve
Withstand voltage	5656VDC from input to output
MTBF	More than 50,000Hrs(25°C,Telecordia SR-332)
EMC	CE EN55011, EN60601-1-2, EN61000-3-2, EN61000-3-3
No load power consumption	<0.1W
Other	USB PD 3.0 ; QC2; QC3 ; FCP / AFC / SCP / Apple 2.4A PPS(Programmable power supply) function Enable (Vo adjust 3.3V~21V) PD: 3.3-21V 2.25A ; QC: 3.6-12V 3A
Safety	(A) UL/cUL (B) TUV/GS (C) TUV/PSE
Warranty	1 year

Standard cable: 1 meter

*: I= (American type FIG 1) or : (European type FIG 2) or : (2pin Australian type FIG 3) or : (British type FIG 4) or : (Chinese type FIG 5) or : (Korean type FIG 6) or : (Argentinian type FIG 7) or : (Japanese type FIG 8) or : (Brazil type FIG 9) or : (India type FIG 10)