

ELJINTEK, INC.

DC TO DC POWER SUPPLY

PSD25-2 (9.0V 2.22A) SPECIFICATION

1) INPUT:

A) INPUT VOLTAGE	11 TO 26VDC
B) OUTPUT VOLTAGE	+9.0 VDC
C) OUTPUT CURRENT	2.22AMPS
D) OUTPUT POWER RANGE	20 WATTS
E) RIPPLE & NOISE	100 mVp-p MAX. (AT 20MHZ BW)
F) LOAD REGULATION	8.55 TO 9.45 VDC (±5% MAXIMUM)
G) OVER VOLTAGE PROTECTION	YES,BY ZENER DIODE
H) OVER CURRENT PROTECTION	YES,AUTO-RECOVERY
I) SHORT CIRCUIT PROTECTION	YES,AUTO-RECOVERY

2) ENVIRONMENTAL:

A) OPERATING TEMPERATURE	0 TO +40°C
B) STORAGE TEMPERATURE	-40 TO +85°C
C) RELATIVE HUMIDITY	5% TO 95% NON-CONDENSING
D) DERATING	FROM +40°C DERATE LINEARLY TO 50% AT +70°C

3) GENERAL:

A) EFFICIENCY	70% MINIMUM AT FULL LOAD
B) HOLD-UP TIME	10m SEC MINIMUM
C) LINE REGULATION	±1% MAXIMUM AT FULL LOAD
E) MEAN TIME BETWEEN FAILURE	100,000 HOURS MIN. AT FULL LOAD AT 25°C AMBIENT