

ELJINTEK, INC.

DC TO DC POWER SUPPLY

PSD60-7 (30V 2A) SPECIFICATION

1) INPUT:

A) INPUT VOLTAGE	11 TO 15VDC
B) OUTPUT VOLTAGE	+30 VDC
C) OUTPUT CURRENT	2 AMPS
D) OUTPUT POWER RANGE	20 WATTS
E) RIPPLE & NOISE	180 mVp-p MAX. (AT 20MHZ BW)
F) LOAD REGULATION	29.40 TO 30.60VDC ($\pm 2\%$ MAXIMUM)
G) OVER VOLTAGE PROTECTION	YES,BY ZENER DIODE
H) OVER CURRENT PROTECTION	YES,AUTO-RECOVERY
I) SHORT CIRCUIT PROTECTION	YES,AUTO-RECOVERY

2) ENVIRONMENTAL:

A) OPERATING TEMPERATURE	0 TO +40°C
B) STORAGE TEMPERATURE	-40 TO +85°C
C) RELATIVE HUMIDITY	5% TO 95% NON-CONDENSING
D) DERATING	FROM +40°C DERATE LINEARLY TO 50% AT +70°C

3) GENERAL:

A) EFFICIENCY	80% MINIMUM AT FULL LOAD
B) HOLD-UP TIME	10m SEC MINIMUM
C) LINE REGULATION	$\pm 1\%$ MAXIMUM AT FULL LOAD
E) MEAN TIME BETWEEN FAILURE	100,000 HOURS MIN. AT FULL LOAD AT 25°C AMBIENT